



## FAIRPLAY-30 ANCHOR HANDLING ASD TUG

MAIN DATA		AUXILIARY SYSTEMS		NAV & RADIO EQUIPMENT	
Type:	Anchor Handling, Offshore, Escort, Harbour, Salvage	Auxiliary Engines:	2x VOLVO Penta each 310kW 1X VOLVO PENTA 116KW -	ECDIS:	2x Chartworld EGLOBE
Built:	2008/ Astilleros Armon			Radar:	Furuno FAR 2117
Manager:	Bugsier-, Reederei- & Bergungs GmbH & Co. KG			Gyro / THD:	Anschütz STD 22
Owner:	Fairplay Towage			GPS:	2x Furuno GP 150
Class:	DNV +100 A5 E1 Tug DNV +MCE1 AUT FF(1)			AIS:	Furuno FA 150
Register & Flag:	Hamburg/ Germany			NAVTEX:	Furuno NX 700
				Echo Sounder:	Furuno FE 700
				Autopilot:	Anschütz Nautopilot NP2015
				Speedlog:	Furuno Ds 80
				Handheld VHF:	4 x ICOM; 4 x UHF
DIMENSIONS		DECK LAYOUT		FIFI & SAFETY	
Length over all:	39,00 m	Bow Winch:	Brusselles Split Drum ASLH 200.59/1S-2-2	Class:	Class 1 (1.200 m³/h)
Breadth over all:	12,70 m	Pull:	50T@10M/MIN; 7T@50M/MIN	Foam Capacity:	16,8 M³
Draft (min/max):	5,50 m / 6,30 m	Holding Force:	200T@1ST LAYER	Breathing App.:	4 Sets with complete outfit
Airdraft (min):	21,00 m	Drum 1:	200M / 52MM / STEEL + STRONGLINE	Rescue Boat:	1X RIGID HULL / 27HP
GT / NT:	787 / 236	Drum 2:	300M / 52MM / STEEL	Rescue System:	MARKUS LIFE NET
PROPULSION SYSTEM		Aft Winch:	BRUSSELLES WATERFALL WINCH SLH 250.123/2-1-1	COMMUNICATION	
Type:	ASD	Pull:	11,5T@31M/MIN-105T@9,4M/MIN	Call Sign:	DFPR2
Main Engines:	2x ABC 12 DZC 1000-166-A	Holding Force:	250T	IMO No.:	9416563
Total Power:	7.213 HP (5.304 kW)	Drum 1:	1150M / 54MM / STEEL	MMSI No.:	211 156 800
Bow Thruster:	1X SCHOTTEL STT110 FP - 200KW -	Drum 2:	120M / 52MM / STEEL WORK WIRE 60m / 52mm / steel work wire	GSM:	+49 151 527 472 30
Stern Thruster:	-	Spare Wire:	900M / 52MM / STEEL	SAT FBB:	+870 773 265 312
PERFORMANCES		Tugger Winch:	2 X 17,5T PULL / 70T HOLD	Mail Port:	fairplay-30@fairplay-towage.com
Bollard Pull:	91,6 TBP cont.	Stern Roller:	4,5 X 1,25M	Mail Sea:	fairplay-30@fairplay-towage.com
Speed:	max 14 kn / eco 9 kn	Karmforks:	200T / < 102MM	SAT C (1):	cpt.fairplay-30@fairplay-towage.com
Cruising Range:	24 days	Tow Pins:	200T / 100T (QUARTER PINS)	SAT C (2):	-
Trade Area:	A1, A2, A3	Smit Bracket:	-	Irridium:	-
Consumption:	7,7m³ / d - ECO-Speed	Crane:	PALFINGER KNUCKLE BOOM CRANE 2,2T@12M	Additional:	-
TANK CAPACITIES		Deck Space:	~ 140M²		
MGO:	438,95 m³	Extensive equipment of shackles, wires, ropes, bridles, chains for deep sea and harbour towage.			
Pot. Water:	62,96 m³ + 1,5 m³ / d prod.	ACCOMODATION			
Lub. Oil:	17,21 m³	Cabins:	4 x Officer single berth cabin		
Sludge:	6,60 m³		3 x Crew double berth cabin		
Bilge Water:	6,63 m³		1 x Hospital single berth		
Sewage:	9,78 m³		Messroom		
			Galley		
		Laundry			
		Total berths:	10 + 1		



Particulars of this unit and inventory believed correct at time of printing but subject to change. Printed November 2022 replacing all previously printed particulars